MATERIAL SAFETY DATA SHEET

PRODUCT NAME: LAMINATE CAULK TINT BASE **HMIS CODES:** H F R P
PRODUCT CODE: LAMINATE CAULK

SECTION I MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Color Fast Industries, Inc
ADDRESS : 350 West H Street
Colton, CA 92324

EMERGENCY PHONE : (888) 600-0476 **DATE PRINTED :** 06/14/99
INFORMATION PHONE : (909) 514-1458 **NAME OF PREPARER :** Dexter Tuttle

SECTION II HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
TITANIUM DIOXIDE	13463-67-7		4
SOLVENT NAPTHA (PETROLEUM) MEDIUM ALIPHATIC	64742-88-7		1

N/A

ABBREVIATIONS: NE - NOT ESTABLISHED, NA - NOT APPLICABLE, [CL] - CEILING LIMIT, D - NUISANCE PARTICLE TVL 10 MG/M3 TOTAL DUST, [C] - CARCINOGEN, [PC] - POTENTIAL CARCINOGEN, DD - INERT OR NUISANCE DUST PEL 15 MG/M3 TOTAL DUST, [1] - NOT ESTABLISHED OR USE STODDARD SOLVENT AS A GUIDE.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A **SPECIFIC GRAVITY (H2O=1):** 1.48
VAPOR DENSITY: Heavier than air **EVAPORATION RATE:** Slower than Ether
COATING V.O.C.: -0.08 lb/gl **MATERIAL V.O.C.:** 0.80 lb/gl
SOLUBILITY IN WATER: PARTIAL
APPEARANCE AND ODOR: WHITE OR COLORED PASTE SLIGHT AMMONIA SMELL

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A **METHOD USED:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A **UPPER:** N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
Not flammable.

UNUSUAL FIRE AND EXPLOSION HAZARDS
N/A

========== SECTION V REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID
Avoid excessive heat

INCOMPATIBILITY (MATERIALS TO AVOID)
No specific incompatabilities.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS